

---


# **IV&V Workshop 2010:**

## **IV&V MADE Testbed Requirements and Configurations**

**David Soto  
September 17, 2010  
L-3 Communications**


**This technical data is controlled under the Export Administration Regulations (EAR) ECCN EAR 99, and may not be exported to foreign persons from Cuba, Iran, North Korea, Sudan and Syria, either in the U.S. or abroad, without a license or exception from the U.S. Department of Commerce.**

# Agenda



- **IV&V Testbed Requirements**
- **ISS Space Station**
  - Description of 1553 Architecture (3-tier system)
- **MADE Testbed Environment**
  - Description of MADE system
- **IV&V Testbed Configurations**


# IV&V Testbed Requirements



- **Simulate single-CSCI and multi-CSCI configurations**
- **Simulate the CSCIs that are in-scope for IV&V**
- **Provide test script development and execution**
- **Compatible with ISS developer's test environments**
- **Run on standard PC computers (Windows)**
  - Remote connection for remote users

*An ISS CSCI (computer software configuration item) is simply an ISS flight software program that is loaded in one of the ISS flight computers.*


# ISS 1553 Architecture (Complex)





77 Terminals  
(BC or RT)

108  
1553 buses

300,000+  
parameters



# Simplistic View of ISS System Hierarchy





Tier 1

Tier 2

Tier 3


An MDM (multiplexer de-multiplexer) is an ISS flight computer.

# Generic MDM Configuration




MDM = ISS flight computer  
CSCI = ISS flight software

# MATE versus MADE



- **MATE (MDM Application Test Environment)**


- Uses flight-equivalent MDM and 1553 hardware
- Runs actual MDM FSW
- ISS environment, sensors, and effectors simulated
- Executes C-scripts (test scripts)
- Real-time and concurrent



*Formal test  
environment  
used by the  
developer*



- **MADE (MDM Application Development Environment)**

- Runs on PC's (Windows)
- Runs actual MDM FSW (small mods to startup code)
- 1553 buses emulated using TCP/IP
- Reuses MATE simulators and configuration data (ISS environment, sensors, effectors, etc.)
- Executes C-scripts (test scripts)
- Not real-time, sequential




*Informal test  
environment  
used by  
developer  
and IV&V*


# Generic MADE Configuration





# MADE Configuration File



 **2000+ lines**  
Configuration

-- LAB\_T3\_SIM\_RTIOIP\_1 Simulation Server Definition

--

START\_SIM LAB\_T3\_SIM\_RTIOIP\_1  
PATH Z:\SVF\_MADE\_CCUCscript  
TYPE MATE  
HOST 191.199.27.115

COMMAND MATE\_Executive.exe

START\_PARAMS

DESCRIPTION Scenario file name

TYPE FILENAME

VALUE ..\Simulations\RTIOIP\_1\_TCE\_X2\_S0R3\made\_flt\_AC\_r3v16\_svf\_m4.scn

DESCRIPTION Simulator Wrapper

TYPE FILENAME

VALUE voss\_c\_crtmain\_IA.bat

END\_PARAMS

END\_SIM

-- Airlock MDM Definition

--

START\_SIM Airlock  
PATH Z:\SVF\_MADE\_CCUCFlight\_Software\Airlock  
TYPE MDM  
HOST 191.199.27.108

COMMAND layer\_1.exe

START\_PARAMS

DESCRIPTION MDM Simulator Config File

TYPE FILENAME

VALUE ALSYSR3V20\_20A\_REVA\_AL1.mdm

END\_PARAMS

END\_SIM


Host computer to run  
simulation specified  
by IP address

MDM FSW file to load  
is specified


Bus connections  
between simulations  
are specified

```
--Bus Type      Bus Name
1553_BUS        LB_SYS-HAB-2
-- Sim Name      Connector
INT_SIM_RTIOIP_3  7
INT1             5 2
INT2             5 2
Airlock          BIA
END_BUS
--
--Bus Type      Bus Name
1553_BUS        UB_LA_3
-- Sim Name      Connector
LAB_T3_SIM_RTIOIP_1  0
LSYS3            0 1
END_BUS
```

# IV&V Testbed Configurations



- **Vertical**
  - Single-MDM configuration (FQT configurations)
    - « Acquired after a CSCI release (post-FQT)
    - « Acquired from CSCI developer
  - Loaded onto single-desktop
  - Meets IV&V's need to independently test CSCI releases
  - Primarily tested using test scripts developed by IV&V
  - Small foot-print to run and execute (one computer)
- **Horizontal**
  - Multi-MDM configuration that simulates complete ISS system
    - « Acquired after a Stage release (post-integration)
    - « Acquired from the Stage integrators (developer)
  - Loaded into IV&V testbed computers (lab)
  - Meets IV&V's needs to independently test HSI (Stage) releases
  - Primarily tested using PCS and MADE graphical user interfaces (GUI)
  - Large foot-print to run and execute (13 computers)
- **Diagonal**
  - Multi-MDM configuration developed by IV&V from FQT single-MDM configurations
  - Meets IV&V's need to test multi-MDM configuration with latest CSCI releases (prior to HSI release)
  - Can be loaded and run in the IV&V testbed lab or single-desktop
  - Primarily tested using test scripts developed by IV&V
  - Medium foot-print to run and execute (one to many computers)



# Diagonal Testbed Demonstration

## ***Next***